

## Safety Standard Certified Ceramic Capacitors

(安全規格認定セラミックコンデンサ)

## Type RA

X1 : 440 Vac(r.m.s.) Y1 : 400 Vac(r.m.s.) X1Y1 : 1500Vdc(ENEC)

Certification Body (認証機関)	Standard No. (規格番号)	Certificate No.* (認定番号)	Expiration date (有効期限)	Attached Page No. (添付ページ番号)
ENEC (VDE)	EN60384-14	40043033	No expiration date (有効期限無し)	h - 1
UL/cUL	UL60384-14/CSA E60384-14	E37921	No expiration date (有効期限無し)	h - 2
CQC	IEC60384-14	CQC16001138225	No expiration date (有効期限無し)	h - 3

\* Above Certified No. may be changed on account of the revision of standards and the renewal of certification.

(\* 認定番号は規格番号の改訂, 取得範囲の変更により変わることがあります。)

**Murata Mfg. Co.,Ltd.**

株式会社 村田製作所

## ZEICHENGENEHMIGUNG MARKS APPROVAL

Murata Mfg. Co., Ltd.  
(Headquarters)  
10-1 Higashikotari 1-Chome  
NAGAOKAKYO-SHI, KYOTO 617-8555  
Japan

ist berechtigt, für ihr Produkt /  
*is authorized to use for their product*

**Festkondensator zur Unterdrückung elektromagnetischer  
Störungen, geeignet für Netzbetrieb**  
***Fixed capacitor for electromagnetic interference  
suppression and connection to the supply mains***

die hier abgebildeten markenrechtlich geschützten Zeichen  
für die ab Blatt 2 aufgeführten Typen zu benutzen /  
*the legally protected Marks as shown below for the types referred to on page 2 ff.*



und/oder - and/or



Geprüft und zertifiziert nach /  
*Tested and certified according to*

DIN EN 60384-14 (VDE 0565-1-1):2014-04; EN 60384-14:2013-08

DIN EN 60384-14/A1 (VDE 0565-1-1/A1):2017-04; EN 60384-14:2013/A1:2016

Das Produkt erfüllt auch die Anforderungen nach /  
*The product also fulfills the requirements of*

EN IEC 60384-14:2023-03

IEC 60384-14:2023

Aktenzeichen: 748200-4670-0062 / 308002

File ref.:

Ausweis-Nr. 40043033

Blatt 1

Certificate No.

Page

Weitere Bedingungen siehe Rückseite und Folgeblätter /  
*further conditions see overleaf and following pages*

Offenbach, 2015-09-29

(letzte Änderung / updated 2023-12-15)

VDE Prüf- und Zertifizierungsinstitut GmbH  
VDE Testing and Certification Institute  
Zertifizierungsstelle / Certification

T. Baumann

VDE Zertifikate sind nur gültig bei Veröffentlichung unter:  
VDE certificates are valid only when published on:

<http://www.vde.com/zertifikat>  
<http://www.vde.com/certificate>

# VDE Prüf- und Zertifizierungsinstitut Zeichengenehmigung

Ausweis-Nr. / Blatt /  
Certificate No. / Page  
40043033 / 2

Name und Sitz des Genehmigungs-Inhabers / *Name and registered seat of the Certificate holder*

Murata Mfg. Co., Ltd. (Headquarters), 10-1 Higashikotari 1-Chome, NAGAOKAKYO-SHI, KYOTO 617-8555,  
JAPAN

Aktenzeichen / *File ref.*

748200-4670-0062 / 308002 / TL3 / KIL

letzte Änderung / *updated*

2023-12-15

Datum / *Date*

2015-09-29

Dieses Blatt gilt nur in Verbindung mit Blatt 1 des Zeichengenehmigungsausweises Nr. 40043033.

*This supplement is only valid in conjunction with page 1 of the Certificate No. 40043033.*

## **Festkondensator zur Unterdrückung elektromagnetischer Störungen, geeignet für Netzbetrieb**

### ***Fixed capacitor for electromagnetic interference suppression and connection to the supply mains***

Typ(en) / *Type(s)*

#### **RA-Series**

Warenzeicheninhaber  
*Trademark holder*

Murata Mfg. Co., Ltd. (Headquarters)

Weitere Einzelheit(en)

Anlage Nr. 200, Nr. 201, Nr. 600, Nr. 700 und Nr. 701 vom  
2023-12-15

*Further details*

*Enclosure no. 200, no. 201, no. 600, no. 700 and no. 701  
dated 2023-12-15*

# VDE Prüf- und Zertifizierungsinstitut Zeichengenehmigung

Ausweis-Nr. / Beiblatt /  
Certificate No. Supplement  
40043033

Name und Sitz des Genehmigungs-Inhabers / *Name and registered seat of the Certificate holder*

Murata Mfg. Co., Ltd. (Headquarters), 10-1 Higashikotari 1-Chome, NAGAOKAKYO-SHI, KYOTO 617-8555,  
JAPAN

Aktenzeichen / *File ref.*

748200-4670-0062 / 308002 / TL3 / KIL

letzte Änderung / *updated*

2023-12-15

Datum / *Date*

2015-09-29

Dieses Beiblatt ist Bestandteil des Zeichengenehmigungsausweises Nr. 40043033.

*This supplement is part of the Certificate No. 40043033.*

## **Festkondensator zur Unterdrückung elektromagnetischer Störungen, geeignet für Netzbetrieb**

***Fixed capacitor for electromagnetic interference  
suppression and connection to the supply mains***

**Fertigungsstätte(n)**

***Place(s) of manufacture***

Referenz/*Reference*

**30002166**

Murata Electronics (Thailand) Ltd.  
Northern Region Ind. Est., 63 Moo 4  
Tambol Ban-Klang Amphur Muang  
LAMPHUN 51000  
THAILAND

# VDE Prüf- und Zertifizierungsinstitut Zeichengenehmigung

Ausweis-Nr. / Infoblatt /  
Certificate No. / Info sheet  
40043033

Name und Sitz des Genehmigungs-Inhabers / *Name and registered seat of the Certificate holder*

Murata Mfg. Co., Ltd. (Headquarters), 10-1 Higashikotari 1-Chome, NAGAOKAKYO-SHI, KYOTO 617-8555, JAPAN

Aktenzeichen / *File ref.*

748200-4670-0062 / 308002 / TL3 / KIL

letzte Änderung / *updated*

2023-12-15

Datum / *Date*

2015-09-29

Dieses Blatt gilt nur in Verbindung mit Blatt 1 des Zeichengenehmigungsausweises Nr. 40043033.

*This supplement is only valid in conjunction with page 1 of the Certificate No. 40043033.*

## **Genehmigung zum Benutzen des auf Seite 1 abgebildeten markenrechtlich geschützten Zeichens des VDE:**

Grundlage für die Benutzung sind die Allgemeinen Geschäftsbedingungen (AGB) der VDE Prüf- und Zertifizierungsinstitut GmbH ([www.vde.com\AGB-Institut](http://www.vde.com\AGB-Institut)). Das Recht zur Benutzung erstreckt sich nur auf die bezeichnete Firma mit den genannten Fertigungsstätten und die oben aufgeführten Produkte mit den zugeordneten Bezeichnungen. Die Fertigungsstätte muss so eingerichtet sein, dass eine gleichmäßige Herstellung der geprüften und zertifizierten Ausführung gewährleistet ist.

Die Genehmigung ist so lange gültig wie die VDE-Bestimmungen gelten, die der Zertifizierung zugrunde gelegen haben, sofern sie nicht auf Grund anderer Bedingungen aus der VDE Prüf- und Zertifizierungsordnung (PM102) zurückgezogen werden muss.

Der Gültigkeitszeitraum einer VDE-GS-Zeichengenehmigung kann auf Antrag verlängert werden. Bei gesetzlichen und / oder normativen Änderungen kann die VDE-GS-Zeichengenehmigung ihre Gültigkeit zu einem früheren als dem angegebenen Datum verlieren.

Produkte, die das Biozid Dimethylfumarat (DMF) enthalten, dürfen gemäß der Kommissionsentscheidung 2009/251/EG nicht mehr in den Verkehr gebracht oder auf dem Markt bereitgestellt werden.

Der VDE-Zeichengenehmigungsausweis wird ausschließlich auf der ersten Seite unterzeichnet.

### **Approval to use the legally protected Mark of the VDE as shown on the first page:**

*Basis for the use are the general terms and conditions of the VDE Testing and Certification Institute ([www.vde.com\terms-institute](http://www.vde.com\terms-institute)). The right to use the mark is granted only to the mentioned company with the named places of manufacture and the listed products with the related type references. The place of manufacture shall be equipped in a way that a constant manufacturing of the certified construction is assured.*

*The approval is valid as long as the VDE specifications are in force, on which the certification is based on, unless it is withdrawn according to the VDE Testing and Certification Procedure (PM102E).*

*The validity period of a VDE-GS-Mark Approval may be prolonged on request. In case of changes in legal and / or normative requirements, the validity period of a VDE-GS-Mark Approval may be shortened.*

*Products containing the biocide dimethylfumarate (DMF) may not be marketed or made available on the EC market according to the Commission Decision 2009/251/EC.*

*The approval is solely signed on the first page.*

# VDE Prüf- und Zertifizierungsinstitut

## Zeichengenehmigung

Name und Sitz des Genehmigungs-Inhabers / *Name and registered seat of the Certificate holder*

Murata Mfg. Co., Ltd., (Headquarters), 10-1 Higashikotari 1-Chome, NAGAOKAKYO-SHI, KYOTO 617-8555, Japan

Dieses Blatt gilt nur in Verbindung mit Blatt 1 des Zeichengenehmigungsausweises Nr. .  
*This supplement is only valid in conjunction with page 1 of the Certificate No.*Rubrik / *Rubric*

341

Ausweis-Nr. /  
*Certificate No.*  
40043033Anlage /  
*Appendix*  
200Aktenzeichen / *File ref.*748200-4670-  
0062/308002/TL3/KILletzte Änderung / *updated*

2023-12-15

Datum / *Date*

2015-09-29

### Festkondensator zur Unterdrückung elektromagnetischer Störungen, geeignet für Netzbetrieb

### *Fixed capacitor for electromagnetic interference suppression and connection to the supply mains*

Typ(en) <i>Type(s)</i>	RA-Series		
Bemessungskapazität <i>Rated capacitance</i>	10pF;15pF;22pF;33pF;47pF;68pF;100pF;150pF;220pF;330pF;470pF; 680pF;1000pF;1500pF;2200pF;3300pF;4700pF		
Bemessungsspannung <i>Rated voltage</i>	X1:AC500V, Y1:AC500V		
Kondensatorklasse und -unterklasse <i>Capacitor class and subclass</i>	X1; Y1		
Grenzabweichung der Bemessungskapazität <i>Tolerance of rated capacitance</i>	±10%(K) oder/or ±20%(M)		
Klimakategorie <i>Climatic category</i>	40/125/21		
Kategorie der passiven Entflammbarkeit <i>Passive flammability category</i>	C		
Keramikart <i>Type of ceramic</i>	SL (10pF bis/to 68pF)		
	B (100 bis/to 680pF) E (1000 bis/to 4700pF)		
Genehmigung für Gleichspannungs- anwendungen nach Anhang H <i>Approval for d.c. applications according to Annex H</i>	<input checked="" type="checkbox"/>	ja <i>yes</i>	Bemessungsgleichspannung DC 1500 V <i>d.c. rated voltage</i>
	<input type="checkbox"/>	nein <i>no</i>	
Genehmigung für Feuchtebeständigkeitsklasse nach Anhang I <i>Approval for humidity robustness grade according to Annex I</i>	<input type="checkbox"/>	IA	21 Tage bei 40 °C / 93 % r.F. mit angelegter Bemessungsspannung <i>21 days at 40 °C / 93 % r.h. with rated voltage applied</i>
	<input type="checkbox"/>	IB	168 Stunden bei 85 °C / 85 % r.F. mit angelegter Bemessungsspannung <i>168 hours at 85 °C / 85 % r.h. with rated voltage applied</i>
	<input type="checkbox"/>	IIA	56 Tage bei 40 °C / 93 % r.F. mit angelegter Bemessungsspannung <i>56 days at 40 °C / 93 % r.h. with rated voltage applied</i>
	<input type="checkbox"/>	IIB	500 Stunden bei 85 °C / 85 % r.F. mit angelegter Bemessungsspannung <i>500 hours at 85 °C / 85 % r.h. with rated voltage applied</i>
	<input type="checkbox"/>	IIIA	56 Tage bei 60 °C / 93 % r.F. mit angelegter Bemessungsspannung <i>56 days at 60 °C / 93 % r.h. with rated voltage applied</i>
	<input type="checkbox"/>	IIIB	1.000 Stunden bei 85 °C / 85 % r.F. mit angelegter Bemessungsspannung <i>1.000 hours at 85 °C / 85 % r.h. with rated voltage applied</i>
	<input checked="" type="checkbox"/>	keine <i>none</i>	
Warenzeicheninhaber <i>Trademark holder</i>	Murata Mfg. Co., Ltd.		



# VDE Prüf- und Zertifizierungsinstitut

## Zeichengenehmigung

Name und Sitz des Genehmigungs-Inhabers / *Name and registered seat of the Certificate holder*

Murata Mfg. Co., Ltd., (Headquarters), 10-1 Higashikotari 1-Chome, NAGAOKAKYO-SHI, KYOTO 617-8555, Japan

Dieses Blatt gilt nur in Verbindung mit Blatt 1 des Zeichengenehmigungsausweises Nr. .  
*This supplement is only valid in conjunction with page 1 of the Certificate No.*Rubrik / *Rubric*

341

Ausweis-Nr. /  
*Certificate No.*

40043033

Anlage /  
*Appendix*

201

Aktenzeichen / *File ref.*

748200-4670-

0062/308002/TL3/KIL

letzte Änderung / *updated*

2023-12-15

Datum / *Date*

2015-09-29

### Festkondensator zur Unterdrückung elektromagnetischer Störungen, geeignet für Netzbetrieb

### *Fixed capacitor for electromagnetic interference suppression and connection to the supply mains*

Typ(en) <i>Type(s)</i>	RA-Series	
Bemessungskapazität <i>Rated capacitance</i>	10pF;15pF;22pF;33pF;47pF;68pF;100pF;150pF;220pF;330pF;470pF; 680pF;1000pF;1500pF;2200pF;3300pF;4700pF	
Bemessungsspannung <i>Rated voltage</i>	X1:AC440V, Y1:AC400V oder/or AC300V oder/or AC250V	
Kondensatorklasse und -unterklasse <i>Capacitor class and subclass</i>	X1; Y1	
Grenzabweichung der Bemessungskapazität <i>Tolerance of rated capacitance</i>	±10%(K) oder/or ±20%(M)	
Klimakategorie <i>Climatic category</i>	40/125/21	
Kategorie der passiven Entflammbarkeit <i>Passive flammability category</i>	C	
Keramikart <i>Type of ceramic</i>	SL (10pF bis/to 68pF) B (100 bis/to 680pF) E (1000 bis/to 4700pF)	
Genehmigung für Gleichspannungs-anwendungen nach Anhang H <i>Approval for d.c. applications according to Annex H</i>	<input checked="" type="checkbox"/>	ja <i>yes</i> Bemessungsgleichspannung DC 1500 V <i>d.c. rated voltage</i>
	<input type="checkbox"/>	nein <i>no</i>
Genehmigung für Feuchtebeständigkeitsklasse nach Anhang I <i>Approval for humidity robustness grade according to Annex I</i>	<input type="checkbox"/>	IA 21 Tage bei 40 °C / 93 % r.F. mit angelegter Bemessungsspannung <i>21 days at 40 °C / 93 % r.h. with rated voltage applied</i>
	<input type="checkbox"/>	IB 168 Stunden bei 85 °C / 85 % r.F. mit angelegter Bemessungsspannung <i>168 hours at 85 °C / 85 % r.h. with rated voltage applied</i>
	<input type="checkbox"/>	IIA 56 Tage bei 40 °C / 93 % r.F. mit angelegter Bemessungsspannung <i>56 days at 40 °C / 93 % r.h. with rated voltage applied</i>
	<input type="checkbox"/>	IIB 500 Stunden bei 85 °C / 85 % r.F. mit angelegter Bemessungsspannung <i>500 hours at 85 °C / 85 % r.h. with rated voltage applied</i>
	<input type="checkbox"/>	IIIA 56 Tage bei 60 °C / 93 % r.F. mit angelegter Bemessungsspannung <i>56 days at 60 °C / 93 % r.h. with rated voltage applied</i>
	<input type="checkbox"/>	IIIB 1.000 Stunden bei 85 °C / 85 % r.F. mit angelegter Bemessungsspannung <i>1.000 hours at 85 °C / 85 % r.h. with rated voltage applied</i>
	<input checked="" type="checkbox"/>	keine <i>none</i>
Warenzeicheninhaber <i>Trademark holder</i>	Murata Mfg. Co., Ltd.	

# Fixed Capacitors for Use in Electronic Equipment - Component

## COMPANY

MURATA MFG CO LTD

COMPONENT BUSINESS UNIT

1-10-1 HIGASIKOTARI

NAGAOKAKYO-SHI, Kyoto 617-8555 Japan

E37921

Marking: Company name or trademark , and model designation.

Note: For additional marking information, refer to the [Guide Information Page](#).

*View model for additional information*

**Class X1 and Class Y2 Capacitors**, Model(s): KJ may be followed by M for +/-20%, K for +/-10%.

**Class X1/Y1 Capacitors**, Model(s): EA may be followed by K ( $\pm 10\%$ ) (for 10~47pF), K ( $\pm 10\%$ ) or M ( $\pm 20\%$ ) (for 100~680pF), M ( $\pm 20\%$ ) (for 1000~2200pF).

**Class X1/Y1 Capacitors**, Model(s): KL may be followed by J ( $\pm 5\%$ ), K ( $\pm 10\%$ ) or M ( $\pm 20\%$ ) for capacitance tolerance.

**Class X1/Y1 Capacitors**, Model(s): RA may be followed by J ( $\pm 5\%$ ), K ( $\pm 10\%$ ) or M ( $\pm 20\%$ ) for capacitance tolerance.

**Class X1/Y1 Capacitors**, Model(s): RB may be followed by K ( $\pm 10\%$ ) or M ( $\pm 20\%$ ) for capacitance tolerance.

**Class X1/Y1 Capacitors, Ceramic Disk Type**, Model(s): KX may be followed by J for +/-5%. K for +/-10%. M for +/-20%.

**Class X1/Y2 Capacitors**, Model(s): IF may be followed by K ( $\pm 10\%$ ).

**Class X1/Y2 Capacitors**, Model(s): SA may be followed by J ( $\pm 5\%$ ), K ( $\pm 10\%$ ) or M ( $\pm 20\%$ ) for capacitance tolerance.

**Class X1/Y2 Capacitors, Ceramic Disk Type**, Model(s): KH may be followed by K for +/-10%. M for +/-20%.

**Class X1/Y2 Capacitors, Ceramic Disk Type**, Model(s): KY may be followed by J for +/-5%. K for +/-10%. M for +/-20%.

**Class X1/Y2 Capacitors, Surface Mount Capacitors**, Model(s): GF series for type GA342 may be followed by J ( $\pm 5\%$ ) (for 10~82pF), K ( $\pm 10\%$ ) (for 100~4700pF).

**Class X1/Y2 Capacitors, Surface Mount Capacitors**, Model(s): GF series for type GA352, GA355 may be followed by J ( $\pm 5\%$ ) (for 10~82pF), K ( $\pm 10\%$ ) (for 100~4700pF).

**Class X1/Y2 Capacitors, Surface Mount Capacitors**, Model(s): ME may be followed by K ( $\pm 10\%$ ) (for 100~4700pF), M( $\pm 20\%$ ) (for 5600~10000pF).

**Class X2 Capacitors**, Model(s): GB+GA35\*\*\*\*GB\*\*\*\*W\*\*\* (\* may be space, 0 to 9, A to Z) with Capacitances of 10000, 15000, 22000, 33000, 47000, or 56000 pF with tolerance K.

Last Updated on 2024-04-27



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."

# Fixed Capacitors for Use in Electronic Equipment Certified for Canada - Component

## COMPANY

### MURATA MFG CO LTD

COMPONENT BUSINESS UNIT

1-10-1 HIGASIKOTARI

NAGAOKAKYO-SHI, Kyoto 617-8555 Japan

E37921

Marking: Company name or trademark , model designation, and the Recognized Component Mark for Canada 

Note: For additional marking information, refer to the [Guide Information Page](#).

*View model for additional information*

**Class X1 and Class Y2 Capacitors**, Model(s): KJ may be followed by M for +/-20%, K for +/-10%.

**Class X1/Y1 Capacitors**, Model(s): EA may be followed by K ( $\pm 10\%$ ) (for 10~47pF), K ( $\pm 10\%$ ) or M ( $\pm 20\%$ ) (for 100~680pF), M ( $\pm 20\%$ ) (for 1000~2200pF).

**Class X1/Y1 Capacitors**, Model(s): RA may be followed by J ( $\pm 5\%$ ), K ( $\pm 10\%$ ) or M ( $\pm 20\%$ ) for capacitance tolerance.

**Class X1/Y1 Capacitors**, Model(s): RB may be followed by K ( $\pm 10\%$ ) or M ( $\pm 20\%$ ) for capacitance tolerance.

**Class X1/Y2 Capacitors**, Model(s): IF may be followed by K ( $\pm 10\%$ ).

**Class X1/Y2 Capacitors**, Model(s): SA may be followed by J ( $\pm 5\%$ ), K ( $\pm 10\%$ ) or M ( $\pm 20\%$ ) for capacitance tolerance.

**Class X1/Y2 Capacitors, Surface Mount Capacitors**, Model(s): GF series for type GA342 may be followed by J ( $\pm 5\%$ ) (for 10~82pF), K ( $\pm 10\%$ ) (for 100~4700pF).

**Class X1/Y2 Capacitors, Surface Mount Capacitors**, Model(s): GF series for type GA352, GA355 may be followed by J ( $\pm 5\%$ ) (for 10~82pF), K ( $\pm 10\%$ ) (for 100~4700pF).

**Class X1/Y2 Capacitors, Surface Mount Capacitors**, Model(s): ME may be followed by K ( $\pm 10\%$ ) (for 100~4700pF), M( $\pm 20\%$ ) (for 5600~10000pF).

Last Updated on 2024-04-27

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."

## Model RA

File Number: E37921

### COMPANY

#### MURATA MFG CO LTD

COMPONENT BUSINESS UNIT

1-10-1 HIGASIKOTARI

NAGAOKAKYO-SHI, Kyoto 617-8555 Japan

### MODEL INFO

RA may be followed by J ( $\pm 5\%$ ), K ( $\pm 10\%$ ) or M ( $\pm 20\%$ ) for capacitance tolerance.

Class X1/Y1 Capacitors

GENERAL										
US Standard	Canadian Standard	Capacitor Class	Voltage (V)	AC or DC	Capacitance	Tolerance (%)	Resistance for RC Devices	Lower Temperature (°C)	Upper Temperature (°C)	Additional Robustness Grades
--	--	X1/Y1	500 Vac	AC	10~4700pF	+/- 20		-40	125	
--	--	X1/Y1	440 / 300 Vac	AC	10~4700pF	+/- 20		-40	125	
--	--	X1/Y1	440 / 250 Vac	AC	10~4700pF	+/- 20		-40	125	
--	--	X1/Y1	440 / 400 Vac	AC	10~4700pF	+/- 20		-40	125	

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."





# CERTIFICATE OF PRODUCT CERTIFICATION

**CERTIFICATE NO.:** CQC16001138225

**Valid from:** Oct.14,2021

**Valid until:**long-term

<b>NAME AND REGISTERED ADDRESS OF THE APPLICANT</b>	Murata Manufacturing Co. 10-1 Higashikotari 1-Chome Nagaokakyo-shi Kyoto-fu 617-8555, Japan
<b>NAME AND REGISTERED ADDRESS OF THE MANUFACTURER</b>	Murata Manufacturing Co. 10-1 Higashikotari 1-Chome Nagaokakyo-shi Kyoto-fu 617-8555, Japan
<b>NAME AND LOCATION OF THE FACTORY</b>	Murata Electronics (Thailand), Ltd. Northern Region Ind. Estate 63 Moo 4, Tambol Ban-Klang Amphur Muang, Lamphun, Thailand
<b>PRODUCT NAME, MODEL AND SPECIFICATION</b>	FIXED CAPACITORS FOR ELECTROMAGNETIC INTERFERENCE SUPPRESSION AND CONNECTION TO THE SUPPLY MAINS RA: 10pF~4700pF a)X1: 500Vac, Y1: 500Vac b)X1: 440Vac, Y1: 300Vac or 250Vac or 400Vac 40/125/21/C ,Tolerance :Type SL(Ceramic) :K( ±10% ) ,Type B(Ceramic) :K or M( ±10% or ±20% ) , Type E(Ceramic) : M ( ±20% ) , Type F(Ceramic) : M ( ±20% )
<b>THE STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS</b>	IEC60384-14:2005

**TYPE OF CERTIFICATION SCHEMES** Type Testing of Product + Initial Factory Inspection + Follow up Factory Inspection

This is to certify that the above mentioned product(s) complies with the requirements of certification rules of CQC11-471112-2015.

Date of original issued: Jan.19,2016

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body.

The certificate information is available through the QR code below or CNCA's website: [www.cnca.gov.cn](http://www.cnca.gov.cn)



SIGNATURE:

谢肇煦



CHINA QUALITY CERTIFICATION CENTRE

